



ref. 99011762

TENT 4X5,5M ARZ20 LANCO WHITE

TENTEN, AFSCHERMINGEN EN SPRINGKUSSENS

Floor area: approx 21 m²

Weight: approx 82 kg

Blow-up time: 1.5 min compressed air kit or 2-4 min electric blower

DESCRIPTION

This ARZ 20 inflatable tent of about 21 square metres is pre-assembled and can be erected by just one person in less than 2 minutes. An overpressure valve prevents excessive pressure in the frame. All load-bearing elements are made of airtight fabric. Due to the modular construction of the frame, it is also possible to exchange individual sections (ridge, eaves and rafters) in the event of serious damage, for example.

- Quick and easy assembly and disassembly
- Modular
- Versatile in use
- All tents can be connected to each other

Application: Triage, Field hospitals / camps, First Aid Post, Decontamination, Command Post, Catering, Weather protection for sensitive equipment, Workshop, Accommodation of traffic victims, ...

TECHNICAL SPECIFICATIONS

- Floor area: approx 21 m²
- Width: 5.50 m
- Length: 3.89 m
- Side height: 2 m
- Ridge height: 2.95 m
- Dimensions (packed): approx. 120 x 87 x 47 cm
- Weight: approx 82 kg
- Exterior colour: white
- Inflatable tent
- Blow-up time: 1.5 min compressed air kit or 2-4 min electric blower
- Working pressure: approx. 0.25 bar
- Max pressure: 0.30 bar

Vanassche Firefighting Engineering

Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

Vanassche Services

Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

- Inflatable frame material: PVC-coated polyester fabric (850 g/m2) with welded seams and reinforced corner joints
- Tent fabric material: one-sided PU-coated polyester fabric (240 g/m2), flame retardant, waterproof and mildew resistant.
- Ground sheet material: double sided PVC coated polyester fabric (550g/m2)
- 2 openings on the sides for the passage of cables, heating hoses, ...
- suspension devices on the frame for lighting, infusion equipment, etc.
- Connection of several tents possible

Content

- 1 Tent, with 2 roll-up and divisible entrances and 2 ventilation hoods in the facade
- 2 Storage bags for tent and accessories
- 6 storm ropes
- 6 pegs (50cm) + 10 pegs (30cm)
- 1 hammer (1.5 kg)
- 1 hand pump
- 1 repair kit
- 1 assembly and maintenance instruction

OPTIONS

- Optional tent fabric: double-sided PVC-coated polyester fabric (530 g/m2)
- Optional groundsheet: double-sided PVC-coated polyester fabric with non-slip relief (850 g / m2)
- Available in 11 colours: white, light grey, beige, yellow, orange, red, blue, dark blue, black, green, dark green
- Electric blower
- Compressed air kit
- Side window
- Compartments
- Inner tent
- Tent lighting
- Tent heating
- Airco



Vanassche Firefighting Engineering

Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

Vanassche Services

Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be