



ref. 99047304

SAFETY TORCH L3000 ATEX WITHOUT CHARGER

HANDLAMPEN

Light output - max: 300 lumens (2 LEDs)

Battery: Rechargeable Lithium

Autonomy: 5h (at max) / 7,5h / 10h

Four user modes available

Tilting head

ATEX

DESCRIPTION

Adalit L-3000 torch is a high quality professional explosion proof torch with large digital display, swivel head and elegant design. Charger is optional.

Four modes are available:

- Full power (2 LEDs, wide and spotlight at the same time)
- Flood light (sufficient light at a short distance - step lighting system for illuminating the ground surface in front of the user's feet)
- Focused light (booster function: illuminating long distances with a large penetrating beam of light)
- Strobe (five different positions)

TECHNICAL SPECIFICATIONS

- Carrying clip to attach to clothing + safety ring.
- Two button switches made of soft touch material, ergonomic and oversized to ensure a simple push of the button.
- Head can be set in 3 positions: 0°, 45°, 90°.
- Battery level indicator in hours and minutes via digital display.
- Low battery warning: Flashing light signal 15 minutes before end of battery.
- Booster function for illuminating long distances with a larger penetrating light beam.
- Technology: LED (2 leds)
- Light output - max: 300 lumens (2 LEDs of 150 lumens each)
- Light intensity: 15 000 candelas
- Light range: 245 m
- Autonomy: 5h (at max) / 7,5h / 10h

Vanassche Firefighting Engineering

Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

Vanassche Services

Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

- Battery: Rechargeable Lithium (3.7 V)
- Length: 225 mm
- Lens diameter: 70 mm
- Dimensions at right angles: 100 x 185 mm
- Colour: yellow with black
- Material: High-Impact plastic, antistatic, resistant to high temperatures and corrosive products
- Protection class: IP67
- Robust: withstands a fall of 4 m.
- Weight: approx. 0,500 kg
- Atex approved zone 0: II 1G Ex ia on is IIC T4 Ga; II 1D Ex ia on is IIIC T85 °C Da; GAS ZONE 0 | 1 | 2; DUST ZONE 20 | 21 | 22

ACCESSORIES

- Neodymium magnet
- Holster
- 99058041: Cone yellow for adalit L3000
- 99047600: Cone red for adalit L3000
- 99024990: Charger 12 V DC L2000/L3000 1 lamp
- 99024991: Charger 24 V DC L2000/L3000 1 lamp
- 99035587: Charger 24/12 V DC L2000/L3000 3 lamps
- 99035588: Charger 24/12 V DC L2000/L3000 5 lamps
- 99094341: Charger 220 V L2000/L3000/L4000/L50 1 lamp
- 99011820: Charger 220 V L2000/L3000 3 lamps
- 99024998: Charger 220 V L2000/L3000 5 lamps



Vanassche Firefighting Engineering

Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

Vanassche Services

Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be