



ref. 99016575

TENT MAXI 4X5M WITHOUT BOTTLE

TENTEN, AFSCHERMINGEN EN SPRINGKUSSENS

Floor area: approx. 20 m²

Weight: approx 45 kg

Charging time: 40 seconds

Inflatable tent, without the use of a pressure release and air hoses

DESCRIPTION

Zieglertent Maxi

Self unfolding and self-erecting emergency tent for various applications. Composed of a waterproof tarpaulin applied to a closed tubular structure. Equipped with a removable ground sheet. Immediately deployable with a minimum of personnel and with one compressed air bottle 6L/300bar.

This tent measures 4m long and 5m wide, allowing you to slide the tent over a vehicle thanks to the removable tarpaulin and still have space to carry out a liberation.

This tent is also incredibly quick and easy to set up: maximum 40 sec. with one 6L/300B compressed air bottle without the use of a shutter and air hoses.

In the event of major emergencies, it is possible to connect tents from other units in the region to your tent by means of a zip.

Free inscription : Fire brigade ... (inscription : 60cm x 127cm)

Application: Environmental protection (changing room for gas suit carriers / storage and exchange of respiratory protection), Technical assistance (protection and transfer of injured persons / care and shock treatment of injured persons / weather protection of persons / equipment / salvage work), ...

In the event of an emergency or repair, a loan is always available.

TECHNICAL SPECIFICATIONS

- Floor area: approx. 20 m²
- Width: 5 m
- Length: 4 m
- Side height: 2 m
- Ridge height: 2.4 m
- Dimensions (packed): approx. 90 x 55 x 40 cm
- Weight: approx 45 kg
- Colour outside: red
- Inflatable tent, without the use of a shutter and air hoses

Vanassche Firefighting Engineering

Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

Vanassche Services

Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

- Charging time: 40 seconds
- Inflatable with 1 compressed air bottle (6 or 6.8 l)
- Max pressure: 0.40 bar
- Material of the inflatable frame: polyamide, coated with polychlorinated butadiene.
- Tent fabric material: Supratex, polyamide coated with acetate cladding (240 g/m²), flame resistant, tear resistant and water resistant.
- Ground tarpaulin material: PVC-coated fabric with good non-slip properties and velcro strips
- openings on the sides for the passage of cables, heating hoses, ...
- 10 suspension devices on the frame for lighting, infusion equipment, etc.
- Version with one window with fly screen and retractable screen
- Multiple tents can be connected without additional accessories (via sewn-in zip)
- Carrying loop on each corner of the rapid deployment marquee for easy manoeuvring by 4 people (or to attach additional ballast)
- 20 fastening points around the quick-insert tent for pegging with pickets
- Fixing points for placing a partition wall so that the rapid deployment marquee can be divided into 2 compartments
- 2 removable opposite doors in the 5m side (door opening: 2.5m x 2m high)
- Blowing up can be done directly on the tent without having to use a pressure reducer, because the tent already has an overpressure valve.

Content

- 1 awning, ventilation hoods in the facade
- Handy transport bag with 2 quick-release fasteners (vehicle belt system) and 2 carrying straps
- storm ropes
- pegs
- 1 repair kit
- 1 assembly and maintenance instruction



Vanassche Firefighting Engineering

Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

Vanassche Services

Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be