



ref. 99031785

PUMP K5SI 220V 330L/MIN+INTERNAL FLOAT

DOMPELPOMPEN MAST

Height of discharge: max. 11 m

Débit maximal : 330 l/min

Passage du sable : 10 mm

Couplage : DSP45 avec boulon

Moteur : 230V - 50 Hz - monophasé

Puissance P1 : 810 W

Protection contre le fonctionnement à sec et sans entretien

DESCRIPTION

Basement drainage pump

Submersible pump Mast type K5 220V with max. flow of 330 l/min, supplied with coupling DSP45 with bolt. This version also has an integrated float.

Applications: For demanding use with dirty water in shafts and wells. Can also be used for pumping fuel oil at room temperature (in accordance with statutory regulations).

Flow rate:

- 330 l/min - 0 m discharge height
- 300 l/min - 2 m discharge height
- 200 l/min - 6 m discharge height
- 0 l/min - 11 m discharge height

TECHNICAL SPECIFICATIONS

- Contains no silicones
- Built-in strain relief
- Motor with thermal winding protection
- Safe dry running
- Maintenance free
- Removable sieve for deeper suction (clip closure)
- Manual/automatic rocker switch with acoustic alarm (80dB).
- Built-in float switch (switch on at 14 cm / switch off at 3 cm)


Vanassche Firefighting Engineering

Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

Vanassche Services

Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

- Pump: Single-stage centrifugal pump
- Height of discharge: max. 11 m
- Maximum flow rate: 330 l/min
- Grit passage: 10 mm
- Exhaust: diameter 1" 1/4
- Coupling: DSP45 with bolt
- Temperature of pumped liquid: max 45°C (permanent), max 80°C (up to 3 min)
- Liquid density: of pumped liquid: max 1,1 kg/dm³
- Acidity of pumped liquid: pH 5-8
- Motor: 230V - 50 Hz - 1-phase
- Power P1: 810 W
- Power P2: 500 W
- Rated current: 3.7 A
- Connection cable: Length 10m (H 07 RN-F 3 G 1.0)
- Plug: Schuko IP 30
- Material carrying handle: Hard plastic (PP) (30% glass fibre reinforced), impact resistant
- Motor housing material: Stainless steel 1.4301
- Pump housing material: Hard plastic (PP) (30% glass fibre reinforced), impact resistant
- Rotor material: Stainless steel 1.4122
- Material range: polyoxymethylene (POM), high hardness, high wear resistance
- Material screws: A2 stainless steel
- Seals material: oil-resistant elastomers NBR quality
- Shaft seal material: 3-fold NBR Perbunan
- Sieve material: Hard plastic (PP) (30% glass fibre reinforced), impact resistant
- Dimensions: Dia175 x H280 mm
- Weight: 7.3 kg



Vanassche Firefighting Engineering

Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

Vanassche Services

Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be