



ref. 99012758

LOW PRESSURE LANCE QUADRAFOG QF1000 6 BAR

STRAALPIJPEN TFT LAGE DRUK

Maximum working pressure: 16 bar

Possible settings flow rate: 285 / 500 / 600 / 800 / 950 (at 6 bar) + flush position

Type: Selectable flow rate at fixed pressure

Valve type: Ball valve

Handles available in 11 colours (standard black)

DESCRIPTION

TFT nozzle - Series Quadrafog

A compact and lightweight nozzle with high performance and robust design. Equipped with a horseshoe handle for operating the ball valve. The nozzle head has a fixed toothed ring and rubber bumper.

The nozzle is equipped with a flow control ring with tactile lock with spring ball (stand-up sensor), making it easy to set the desired flow rate. There is also a tactile marking on the head that clearly indicates the Flashover positioning.

Suitable for mounting on a low pressure line.

TECHNICAL SPECIFICATIONS

- Range: Low pressure nozzle of the American type
- Type: Selectable flow rate at fixed pressure
- Flow rate: 285 - 950 l/min (at 6 bar)
- Flow selection via flow ring
- Possible settings flow rate: 285 / 500 / 600 / 800 / 950 (at 6 bar) + flush position
- Pressure Pr: 6 bar
- Pressure Pn: 16 bar
- Bursting pressure: 70 bar
- Pressure regulation: No
- Range: 48m at 950 l/min
- Clutch: 2.5" BSP F (rocker)
- Including DSP 70 coupling
- Swivel joint (360°): Yes

Vanassche Firefighting Engineering

Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be


Vanassche Services

Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

- Filter (suction sieve): No
- Valve type: Ball valve
- Valve material: stainless steel
- Handle: Horseshoe handle
- Tooth wreath: Fixed - precision ground metal fog teeth
- Protective bumper: Yes
- Jet pattern: Infinitely adjustable jet pattern from full jet to water screen 130°
- Position sensor (spring loaded) on flow setting and beam pattern
- Gun grip: Yes
- Nozzle material: hard-anodised aluminium
- Standardisation: EN15182-2 Type 3
- Dimensions: 330 x 255 x 120 mm
- Weight : 2.97 kg

ACCESSORIES AND OPTIONS

- Handles available in 11 colours
- 99030492: Foam insert Heavy foam (Low expansion)



Vanassche Firefighting Engineering

Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

Vanassche Services

Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be