

ref. 99053671

EMULSIFIER HIFOAM S2 WAS 200L /L

SCHUIMPRODUCTEN KLASSE B

DESCRIPTION

Synthetic multi-range foam (Class B)

Used for extinguishing fuels (hydrocarbons), covering fires and filling rooms small or large.

Note : former name = emulsor S.

TECHNICAL SPECIFICATIONS

Typical physiochemical properties at 20°C

- Type: synthetic concentrate
- Can be rinsed with: clean water, brackish water or salt water
- Ratio: 2-6 %
- Density: 1,020 g/ml $\pm$ 0,01
- Acidity: pH 7.0 $\pm$ 0.5
- Surface tension (6% solution): < 30 mN/m
- Freezing point: -9°C
- Packaging: 200 litre drums

(price per litre)

Vanassche Firefighting Engineering

Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

Vanassche Services

Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be