



ref. 99059653

XX MOBILE FAN MGX L105 SPEED

VENTILATOREN GROOT DEBIET

Max Capacity: 600 000 m³/h

Propeller diameter : 1 050 mm

Mounted on a single-axle trailer

DESCRIPTION

DE MGX L105 is the smaller brother of the L125 and specially designed for the municipal fire brigade. It has sufficient energy reserves for the ventilation of underground car parks, industrial facilities, hospitals, schools and shopping centres.

It also has a very high suction power when using the ventilation hose system and the patented adapter. Powered by a reliable 3-cylinder motor, it sets new standards in its class thanks to its compact dimensions and low weight. The compact height (< 2 m) ensures that the L105 even gets under a normal garage door!

TECHNICAL SPECIFICATIONS

Fan

- Easy to handle by one person
- Max Capacity: 600 000 m³/h
- Nominal capacity: 145 000 m³/h
- Axial force: approximately 1 600 N
- Max airspeed: 50 m/s
- Rotational speed rotor blade: approx. 2 000 rpm
- Propeller diameter: 1 050 mm
- Outer diameter: 1 340 mm
- Length Turbine sheath: 720 mm
- Engine: 3-cylinder petrol engine - air-cooled
- Motor type: EB2
- Engine power: 55 kW
- Torque: 130 Nm
- Fuel tank: 45 l
- Electric starter for the engine, with ignition key.

Vanassche Firefighting Engineering

Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

Vanassche Services

Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

- Easy access to the starter battery via a maintenance opening.
- In case the starter battery is empty, the MVU can be started externally via the jump-start facility.
- Drive: toothed belt (maintenance-free)
- Propeller: glass fibre reinforced polyamide, 8 blades
- Turbine jacket: glass fibre reinforced plastic, shell-shaped design for less vibration
- Safety grilles on both sides of the casing in accordance with EN 294
- Operation: remote control with TFT display with emergency stop and 5m cable

Mounted on a single-axle trailer

- Gross vehicle weight: 750 kg
- Including material case with toolkit
- Including handles
- Including 2 support legs
- Dimensions (l x w x h): approx. 3400 x 1850 x 1950 mm
- Net weight trailer with fan : 620 kg

ACCESSORIES AND OPTIONS

Tilting option:

- Tilt angle: +15° / -15°
- Operation: hydraulic, with hand pump

Option Water fog system:

- 10 integrated nozzles
- Water yield: 200 l/min at 7 bar
- Max pressure: 10 bar

Option Ventilation hose system:

- Air outlet: 35 000 m³/h
- Diameter: 800 mm
- Adapter: 1 piece including 3m hose
- Mounting: Pressure or suction side
- Length: 1 x 15m (standard package), expandable

Option roll plastic air hose:

- Diameter: 1 165 mm
- Mounting: Pressure side
- Length: 100 m

Trailer options:

- Integrated battery charger ((230 V /12 V)
- Height adjustable drawbar
- LED work light
- Rack for ventilation hose system



Vanassche Firefighting Engineering

Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

Vanassche Services

Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be



Vanassche Firefighting Engineering

Brugsesteenweg 8
B-8531 Harelbeke
+32 (0) 56 710 130
info@vanassche-fire.be
BE 0415.345.684
RPR Gent - Afdeling Kortrijk
vanassche-fire.be

Vanassche Services

Brugsestraat 153
B-8531 Harelbeke
+32 (0) 56 738 188
services@vanassche-fire.be
BE 0473.397.315
RPR Gent - Afdeling Kortrijk
vanassche-fire.be